

SERIE 21

## 60YBISB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 150mm ean 27974

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793279741 **EAN5:**27974 **Article code:**21060BF150OCN



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 500 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Ochre
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted