ALDO VALSECCHI S.P.A.
Via XX Settembre, 107
28883 Gravellona Toce (VB) – Italia

www.avo.it
+39 0323 86 99 11
export@avo.it

SERIE 17

32B

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 20356

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:
Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:
Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793203562 **EAN5:**20356 **Article code:**12032B0160NBA

Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 400 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	400
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized