

SERIE 17

## 32B

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 20357

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:**  
Industry

**Description:**

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793203579

**EAN5:**20357

**Article code:**12032B0160NRA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 400 DaN

- Concrete
- Stoneware

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

## Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	400
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized