

SERIE 21

## 60YB

**AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 20386**

**Material:** Thermoplastic  
Polyurethane

**Core:**  
Polyamide 6

**Application field:**  
Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793203869

**EAN5:**20386

**Article code:**21060B0160OCN



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 500 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 160                        |
| Band width (mm)             | 50                         |
| Hub width (mm)              | 55                         |
| Hub version                 | Ball bearing               |
| Wheel hole (mm)             | 20                         |
| Bearing seat (mm)           | 47X14                      |
| Dynamic load capacity (DaN) | 500                        |
| Colour                      | Ochre                      |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 97                         |

## Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 57                                        |
| Ground clearance (mm)      | 240                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 630                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle                                      |
| Brake                      | /                                         |
| Plain axle                 | 22X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Black painted                             |