

SERIE 17

31A

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 25874

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Polyurethane, Stainless steel

EAN13:8018793258746 **EAN5:**25874 **Article code:**12031A0160NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 160 |
| Band width (mm) | 40 |
| Hub width (mm) | 55 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | 47X14 |
| Dynamic load capacity (DaN) | 300 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | 140X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 11X16 |
| Offset (mm) | / |
| Ground clearance (mm) | 197 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 380 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |