

SERIE 61

432B

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 27321

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793273213 **EAN5:**27321 **Article code:**12432B0160NRA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 400 DaN

- Concrete
- Stoneware

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	400
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized