

SERIE 17G-S

31ANTG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 160mm ean 27491

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793274913 **EAN5:**27491 **Article code:**128310A160NBG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 300 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	197
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized