Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

32**B** 

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 06544

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

## **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

**EAN13**:8018793065443 **EAN5**:06544 **Article code**:12032B0175NBA



**Features** 

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 500 DaN

Rotation: Plain bore Hardness scale: Shore A Hardness: 97

## **Flooring**

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	175
Band width (mm)	45
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	500
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	231
Castor hole (mm)	1
Static load capacity (DaN)	630
Structure	Swivel
Version	Axle
Brake	1
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized