

SERIE 17

32BIS

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 06551

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793065511 **EAN5:**06551 **Article code:**120320F175NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 500 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	175
Band width (mm)	45
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	238
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized