

SERIE 17

32BISB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 10733

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793107334 **EAN5:**10733 **Article code:**12032BF175NBA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 500 DaN

• Concrete

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

• Stoneware

Flooring

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 175 |
| Band width (mm) | 45 |
| Hub width (mm) | 58 |
| Hub version | Plain bore |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 500 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 57 |
| Ground clearance (mm) | 231 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 630 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 25X65 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |