Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

31ANTB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 11038

Material: Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793110389 **EAN5**:11038 **Article code**:12031BA175NCA



Features

Minimum temperature: -20 Maximum tempera

Maximum temperature: 80 Dynamic load capacity: 300 DaN

Rotation: Ball bearing Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	175
Band width (mm)	45
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	205
Castor hole (mm)	1
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized