Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17

## 31ANTB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 11039

**Material:** Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

## Medium duty castors:

Made of zino-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Hardness scale: Shore A

Product line: Stainless steel, Polyurethane

**EAN13**:8018793110396 **EAN5**:11039 **Article code**:12031BA175NRA



**Features** 

Minimum temperature: -20 Maximum temperature: 80

ature: 80 Dynamic load capacity: 300 DaN

Hardness: 97

**Flooring** 

ConcreteStoneware

## Wheel data

Rotation: Roller bearing

Diameter (mm)	175
Band width (mm)	45
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	300
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized