

SERIE 61

432

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 27235

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Polyurethane, Stainless steel

EAN13:8018793272353 **EAN5:**27235 **Article code:**1243200175NBA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 500 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 175 |
| Band width (mm) | 45 |
| Hub width (mm) | 58 |
| Hub version | Plain bore |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 500 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | 135X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 13X16 |
| Offset (mm) | 57 |
| Ground clearance (mm) | 238 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 630 |
| Structure | Swivel |
| Version | Plate |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |