

SERIE 17G-S

31ANTBG-S

AVO - Wheel made of thermoplastic polyurethane with steel castor for industry, diameter 175mm ean 27554

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Scope: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793275545

EAN5:27554

Article code:12831BA175NRG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 175 |
| Band width (mm) | 45 |
| Hub width (mm) | 58 |
| Hub version | Roller bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 300 |
| Colour | Grey |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|--------------------------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 55 |
| Ground clearance (mm) | 205 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 380 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Front |
| Plain axle | 22X50 |
| Stem type | Stem(on request threaded stem) |
| Finishing | Galvanized |