

SERIE 17G-S

## 31ANTBG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 175mm ean 27554

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyurethane, Stainless steel

**EAN13:**8018793275545 **EAN5:**27554 **Article code:**12831BA175NRG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 300 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Concrete
- Stoneware

### Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 175                        |
| Band width (mm)             | 45                         |
| Hub width (mm)              | 58                         |
| Hub version                 | Roller bearing             |
| Wheel hole (mm)             | 20                         |
| Bearing seat (mm)           | /                          |
| Dynamic load capacity (DaN) | 300                        |
| Colour                      | Grey                       |
| Material                    | Thermoplastic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 80                         |

### Support data

|                            |  |
|----------------------------|--|
| Plate size (mm)            | /  |
| Plate hole spacing (mm)    | /  |
| Plate hole size (mm)       | /  |
| Offset (mm)                | 55   |
| Ground clearance (mm)      | 205  |
| Castor hole (mm)           | /  |
| Static load capacity (DaN) | 380  |
| Structure                  | Swivel                                       |
| Version                    | Axle with brake                              |
| Brake                      | Front  |
| Plain axle                 | 22X50  |
| Stem type                  | Stem(on request threaded stem)<br>Plain axle |
| Finishing                  | Galvanized                                   |