

SERIE 17

32BISB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 10737

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793107372 **EAN5:**10737 **Article code:**12032BF200NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 600 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	600
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized