

SERIE 17

32BIS

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 10751

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793107518

EAN5:10751

Article code:120320F200NRA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 600 DaN

- Concrete
- Stoneware

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	600
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	750
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized