

SERIE 21

60A

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 17529

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Polyurethane

EAN13:8018793175296

EAN5:17529

Article code:12060A0200OCN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	57
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Ochre
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	/
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	1000
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized