

SERIE 17CD

32-CD

AVO - Wheel made of thermoplastic polyurethane with steel castor for industry, diameter 200mm ean 20285

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:

Wheel coated with conductive injection polyurethane thread 97 Shore A with conductive polyamide 6 centre. Hub on roller bearings, plain bore or shielded ball bearings assembled with central spacer. The 17CD wheel can be combined with all medium and heavy duty castors.

Heavy-Duty Castors:

Product line: Antistatic/Conductive

EAN13:8018793202855 **EAN5:**20285 **Article code:**C203200200NCA



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	400
Colour	Red
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized