

SERIE 61

## 431ANT

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 27162

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793271622 **EAN5:**27162 **Article code:**124310A200NBA



### Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 300 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

### Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized