Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17G-S

# 31BISG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 27484

**Material:** Thermoplastic Polyurethane

Core: Polyamide 6 Application field:

olyamide 6 Industry

#### Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut.

Product line: Polyurethane, Stainless steel

**EAN13**:8018793274845 **EAN5**:27484 **Article code**:128310F200NRG



#### **Features**

Minimum temperature: -20 Maximum ter

Maximum temperature: 80 Dynamic load capacity: 300 DaN

Hardness scale: Shore A Hardness: 80

## **Flooring**

- Concrete
- Stoneware

#### Wheel data

Rotation: Roller bearing

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

### Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	1
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized