Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17G-S

## 31ANTFG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 27572

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

## Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

**EAN13**:8018793275729 **EAN5**:27572 **Article code**:12831FA200NRG



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 300 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 80

ConcreteStoneware

## Wheel data

Diameter (mm)	200
Band width (mm)	500
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	1
Stem type	1
Finishing	Galvanized