

SERIE 21-S

## 60BISB-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 200mm ean 27973

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:**  
Industry

**Description:**

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyurethane

**EAN13:** 8018793279734

**EAN5:** 27973

**Article code:** 12S60BF200BCN



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 800 DaN

- Concrete
- Stoneware

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

## Wheel data

<b>Diameter (mm)</b>	200
<b>Band width (mm)</b>	57
<b>Hub width (mm)</b>	60
<b>Hub version</b>	Ball bearing
<b>Wheel hole (mm)</b>	25
<b>Bearing seat (mm)</b>	47X14
<b>Dynamic load capacity (DaN)</b>	800
<b>Colour</b>	Blue
<b>Material</b>	Thermoplastic Polyurethane
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	97

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	57
<b>Ground clearance (mm)</b>	244
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	1000
<b>Structure</b>	Swivel
<b>Version</b>	Axle with brake
<b>Brake</b>	Rear
<b>Plain axle</b>	25X65
<b>Stem type</b>	Plain axle Stem(on request threaded stem)
<b>Finishing</b>	Galvanized