

SERIE 5L

5

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 60mm ean 20495

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A or 80 Shore A (5L-S) and Polyamide 6 centre. Hub on plain bore or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793204958 **EAN5:**20495 **Article code:**1200500060NCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 60 |
| Band width (mm) | 25 |
| Hub width (mm) | 28 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 8 |
| Bearing seat (mm) | 32X10 |
| Dynamic load capacity (DaN) | 70 |
| Colour | Grey |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 89 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 100 |
| Structure | Swivel |
| Version | Plate |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |