

SERIE 5L

5A

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 60mm ean 20498

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A or 80 Shore A (5L-S) and Polyamide 6 centre. Hub on plain bore or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793204989 **EAN5:**20498 **Article code:**12005A0060NCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	60
Band width (mm)	25
Hub width (mm)	28
Hub version	Ball bearing
Wheel hole (mm)	6
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	70
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	89
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized