

SERIE 5L

## 5ANTB

**AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 60mm ean 25667**

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Scope:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A or 80 Shore A (5L-S) and Polyamide 6 centre. Hub on plain bore or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** Polyurethane, Stainless steel

**EAN13:**8018793256674

**EAN5:**25667

**Article code:**12005BA060NC4



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 70 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 97

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	60
Band width (mm)	25
Hub width (mm)	29
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	70
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	87
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	10X30
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized