Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 61

431ANT

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 60mm ean 27169

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: Stainless steel, Polyurethane

EAN13:8018793271691 **EAN5**:27169 **Article code**:124310A060NCB



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 70 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 97

• Concrete

Stoneware

Wheel data

Diameter (mm)	60
Band width (mm)	24
Hub width (mm)	10
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	70
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	89
Castor hole (mm)	1
Static load capacity (DaN)	100
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	1
Stem type	1
Finishing	Galvanized