

SERIE 17G-S

31ANTBG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 60mm ean 27540

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Scope: Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793275408

EAN5:27540

Article code:12831BA061NBG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 80

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 60 |
| Band width (mm) | 24 |
| Hub width (mm) | 39 |
| Hub version | Plain bore |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 70 |
| Colour | Grey |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 37 |
| Ground clearance (mm) | 87 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 100 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Front |
| Plain axle | 20X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |