

SERIE 17

31

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 10722

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793107228

EAN5:10722

Article code:1203100080NCA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	120
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	108
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized