

SERIE 17

32B

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 13064

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded red Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Polyurethane, Stainless steel

EAN13:8018793130646 **EAN5:**13064 **Article code:**12032B0080NBA



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

- Concrete
- Stoneware

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 97

Flooring

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	36
Ground clearance (mm)	114
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized