

SERIE 5L

5ANTB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 18115

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A or 80 Shore A (5L-S) and Polyamide 6 centre. Hub on plain bore or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793181150

EAN5:18115

Article code:12005BA080NCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 100 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	48
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized