Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 17G-S

31ANTFG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 19049

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyurethane

EAN13:8018793190497 **EAN5**:19049 **Article code**:12831FA080NBG



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 120 DaN

Rotation: Plain bore Hardness scale: Shore A Hardness: 80

ConcreteStoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	1
Stem type	1
Finishing	Galvanized