

SERIE 61

## 431ANTB

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 27183

**Material:** Thermoplastic Polyurethane

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

**Product line:** Stainless steel, Polyurethane

**EAN13:**8018793271837    **EAN5:**27183    **Article code:**12431BA080NRA



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 120 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore A    **Hardness:** 97

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Blue
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized