Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 61

432BIS

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 27258

Material: ThermoplasticCore:Application field:PolyurethanePolyamide 6Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793272582 **EAN5**:27258 **Article code**:124320F080NRA



Features Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 120 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 97

ConcreteStoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	120
Colour	Red
Material	Thermoplastic Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	97

Support data

Plate hole spacing (mm) 080X060 Plate hole size (mm) 9X12 Offset (mm) 36
Offset (mm) 36
Ground clearance (mm) 118
Castor hole (mm) /
Static load capacity (DaN) 150
Structure Swivel
Version Plate with brake
Brake Rear
Plain axle /
Stem type /
Finishing Galvanized