

SERIE 61

432B

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 27311

Material: Thermoplastic Polyurethane

Core: Polyamide 6

Application field: Industry

Description:

Wheel coated with injection-moulded Polyurethane tread, 97 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793273114 **EAN5:**27311 **Article code:**12432B0080NCB



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 97

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 30 |
| Hub width (mm) | 30 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 32X10 |
| Dynamic load capacity (DaN) | 120 |
| Colour | Red |
| Material | Thermoplastic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 97 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 36 |
| Ground clearance (mm) | 114 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 150 |
| Structure | Swivel |
| Version | Axle |
| Brake | / |
| Plain axle | 22X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |