

SERIE 17G-S

32BISG-S

AVO - Wheel with thermoplastic polyurethane and steel castor for industry, diameter 80mm ean 27595

Material: Thermoplastic
Polyurethane

Core:
Polyamide 6

Application field:
Industry

Description:

Wheel coated with injection-moulded soft Polyurethane tread, 80 Shore A and Polyamide 6 centre. Hub on plain bore, roller bearing or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyurethane

EAN13:8018793275958

EAN5:27595

Article code:128320F080NCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 120 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Thermoplastic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	9X12
Offset (mm)	36
Ground clearance (mm)	118
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized