

SERIE 16NX-AM

16NX-AM

AVO - Wheel with non-marking rubber tyre for industry, diameter 100mm ean 19115

Material: Non-marking
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on stainless steel roller bearing, shielded stainless steel ball bearings assembled with central spacer.

Product line: Stainless steel

EAN13:8018793191159

EAN5:19115

Article code:8315X16N1042F



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 200 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/