

SERIE 112AM

# 112AM

AVO - Wheel with non-marking rubber tyre for industry, diameter 160mm ean 05363

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Product line:** Rubber tyre

**EAN13:**8018793053631

**EAN5:**05363

**Article code:**03112001600RG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 150 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 160                     |
| Band width (mm)             | 40                      |
| Hub width (mm)              | 55                      |
| Hub version                 | Roller bearing          |
| Wheel hole (mm)             | 17                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 150                     |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 80                      |

## Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | / |
| Plate hole spacing (mm)    | / |
| Plate hole size (mm)       | / |
| Offset (mm)                | / |
| Ground clearance (mm)      | / |
| Castor hole (mm)           | / |
| Static load capacity (DaN) | / |
| Structure                  | / |
| Version                    | / |
| Brake                      | / |
| Plain axle                 | / |
| Stem type                  | / |
| Finishing                  | / |