

SERIE 16NX-AM

66XANT-AM

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 100mm ean 19557

Material: Non-marking
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on stainless steel roller bearing, shielded stainless steel ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793195577

EAN5:19557

Article code:00X660A101NRG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 150 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel