

SERIE 139L

140LXF

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 100mm ean 22757

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

Product line: Stainless steel, Rubber tyre

EAN13:8018793227575 **EAN5:**22757 **Article code:**06140F0100LCX



Features

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 100 DaN

Rotation: Stainless steel ball bearing

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	32
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	12
Static load capacity (DaN)	120
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel