

SERIE 112B-AM

## 90XANTB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 100mm ean 24386

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793243865 **EAN5:**24386 **Article code:**02090XBA101BG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 70 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 100                     |
| Band width (mm)             | 30                      |
| Hub width (mm)              | 40                      |
| Hub version                 | Plain bore              |
| Wheel hole (mm)             | 12                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 70                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 83                      |

### Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | /                        |
| Plate hole spacing (mm)    | /                        |
| Plate hole size (mm)       | /                        |
| Offset (mm)                | 37                       |
| Ground clearance (mm)      | 126                      |
| Castor hole (mm)           | /                        |
| Static load capacity (DaN) | 90                       |
| Structure                  | Swivel                   |
| Version                    | Axle with brake          |
| Brake                      | Front                    |
| Plain axle                 | 12X30                    |
| Stem type                  | Threaded axle            |
| Finishing                  | AISI 304 stainless steel |