

SERIE 16NX-AM

## 66XANT-AM

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 125mm ean 20999

**Material:** Non-marking Rubber tyre

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on stainless steel roller bearing, shielded stainless steel ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

**Product line:** Stainless steel

**EAN13:**8018793209991

**EAN5:**20999

**Article code:**00X660A127NRG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 170 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Stoneware
- Wood

### Wheel data

Diameter (mm)	125
Band width (mm)	36
Hub width (mm)	50
Hub version	Stainless steel roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

### Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel