

SERIE 139L

140LXANT

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 125mm ean 22987

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

Medium duty castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

EAN13:8018793229876 **EAN5:**22987 **Article code:**061400A125LCX



Features

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 105 DaN

Rotation: Stainless steel ball bearing

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	105
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	154
Castor hole (mm)	/
Static load capacity (DaN)	125
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel