

SERIE 139L

# 140LXANTF

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 125mm ean 22989

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and front brake. Dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793229890 **EAN5:**22989 **Article code:**06140FA125LCX



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 105 DaN

**Rotation:** Stainless steel ball bearing

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	105
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	152
Castor hole (mm)	12
Static load capacity (DaN)	125
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel