Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 139L

140LXB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 125mm ean 25641

Material: Non-marking Rubber tyre

Polypropylene

Application field:

pylene Industry

Description:

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem. Dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

EAN13:8018793256414 EAN5:25641 Ar

Article code:06140B0125LCX



Features

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 105 DaN

Rotation: Stainless steel ball bearing Hard

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

Diameter (mm)	125
Diameter (mm)	123
Band width (mm)	32
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	1
Dynamic load capacity (DaN)	105
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	152
Castor hole (mm)	1
Static load capacity (DaN)	105
Structure	Swivel
Version	Axle
Brake	I
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel