

SERIE 112B-AM

# 90X

**AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 160mm ean 16525**

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Scope:** Industry

**Description:**

Wheel with grey no-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

**Product line:** Stainless steel, Rubber tyre

**EAN13:**8018793165259 **EAN5:**16525 **Article code:**02090X01600BG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 140 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	160
<b>Band width (mm)</b>	40
<b>Hub width (mm)</b>	58
<b>Hub version</b>	Plain bore
<b>Wheel hole (mm)</b>	20
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	140
<b>Colour</b>	Grey
<b>Material</b>	Non-marking Rubber tyre
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	83

## Support data

<b>Plate size (mm)</b>	140X110
<b>Plate hole spacing (mm)</b>	105X080
<b>Plate hole size (mm)</b>	11X16
<b>Offset (mm)</b>	55
<b>Ground clearance (mm)</b>	197
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	180
<b>Structure</b>	Swivel
<b>Version</b>	Plate
<b>Brake</b>	/
<b>Plain axle</b>	/
<b>Stem type</b>	/
<b>Finishing</b>	AISI 304 stainless steel