

SERIE 112B-AM

## 90XA

**AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 160mm ean 16569**

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, fixed.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793165693

**EAN5:**16569

**Article code:**02090XA1600BG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 140 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 160                     |
| Band width (mm)             | 40                      |
| Hub width (mm)              | 58                      |
| Hub version                 | Plain bore              |
| Wheel hole (mm)             | 20                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 140                     |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 83                      |

## Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | 140X110                  |
| Plate hole spacing (mm)    | 105X080                  |
| Plate hole size (mm)       | 11X16                    |
| Offset (mm)                | /                        |
| Ground clearance (mm)      | 197                      |
| Castor hole (mm)           | /                        |
| Static load capacity (DaN) | 260                      |
| Structure                  | Fixed                    |
| Version                    | /                        |
| Brake                      | /                        |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |