

SERIE 16NX-AM

## 66XANTF-AM

**AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 160mm ean 20685**

**Material:** Non-marking  
Rubber tyre

**Core:** Polyamide  
6

**Application field:**  
Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on stainless steel roller bearing, shielded stainless steel ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and front brake.

**Product line:** Stainless steel

**EAN13:**8018793206853

**EAN5:**20685

**Article code:**00X66FA160NRG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 300 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Stoneware
- Wood

### Wheel data

|                             |                                |
|-----------------------------|--------------------------------|
| Diameter (mm)               | 160                            |
| Band width (mm)             | 50                             |
| Hub width (mm)              | 58                             |
| Hub version                 | Stainless steel roller bearing |
| Wheel hole (mm)             | 20                             |
| Bearing seat (mm)           | /                              |
| Dynamic load capacity (DaN) | 300                            |
| Colour                      | Grey                           |
| Material                    | Non-marking Rubber tyre        |
| Box pieces                  | /                              |
| Hardness scale              | Shore A                        |
| Hardness                    | 68                             |

### Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | /                        |
| Plate hole spacing (mm)    | /                        |
| Plate hole size (mm)       | /                        |
| Offset (mm)                | 55                       |
| Ground clearance (mm)      | 194                      |
| Castor hole (mm)           | 16                       |
| Static load capacity (DaN) | 380                      |
| Structure                  | Swivel                   |
| Version                    | Bolt hole with brake     |
| Brake                      | Front                    |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |