

SERIE 180X

250XA

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 50mm ean 25427

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material. Hub on plain bore.

Furniture Castors:

Made of pressed stainless steel AISI 304, fixed.

Product line: Stainless steel

EAN13:8018793254274 **EAN5:**25427 **Article code:**22250A0050X0G



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 40 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 85

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

Wheel data

| | |
|-----------------------------|-------------------------|
| Diameter (mm) | 50 |
| Band width (mm) | 23 |
| Hub width (mm) | 29 |
| Hub version | Plain bore |
| Wheel hole (mm) | 8 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 40 |
| Colour | Grey |
| Material | Non-marking Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 85 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | 060X060 |
| Plate hole spacing (mm) | 042X042 |
| Plate hole size (mm) | 6,5X10 |
| Offset (mm) | / |
| Ground clearance (mm) | 75 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 60 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |