

SERIE 180X

250XBISF

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 50mm ean 27964

Material: Non-marking Rubber tyre

Core: Polypropylene

Scope: Industry

Description:

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material.

Furniture Castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole, front brake and locking device to stop both wheel and rotation.

Product line: Stainless steel

EAN13:8018793279642 **EAN5:**27964 **Article code:**22250FA051X0G



Features

Minimum temperature: -20	Maximum temperature: 80	Dynamic load capacity: 50 DaN
Rotation: Plain bore	Hardness scale: Shore A	Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

Wheel data

Diameter (mm)	50
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	27
Ground clearance (mm)	75
Castor hole (mm)	10
Static load capacity (DaN)	70
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel